BASE MICROPHONE

- ***ECHO & REVERBERATION**
- *DUAL ROGER BEEP
- *PREAMPLIFIED



Technical Details:

- * Echo/Reverb: Variable Volume and Delay with Sliders Accessible on Top of the Mic
- * Amplification Control: Variable Modulation Control Allows you Adjust the Maximum Control on How Loud You Want To Be.
- *Push-To-Talk Lock Switch
- * Adjustable Swivel Gooseneck Boom
- * TX/Battery Indicator LED
- *VU Modulation Meter
- *Roger Beep with Switch
- * Operates on 9V Battery Battery (not included)

*Length: 6 3/8"
*Width: 4 7/8"
*Height: 1 1"
*4" Coiled Cord

*Type of Microphone: Electric

* Sensitivity: -30dB

* Output Level: From 0V to 1.4V * Frequency Response: 200-3000Hz

* Output Impedance: 1K Ohm

* Load Impedance: 50 Ohm-100K Ohm

* Echo Delay Time: 50-200mS Adjustable

* Roger Beep TX Time: 1.2 Seconds Approximately

* Current Drain: 8mA (TX)

* Power Supply: One 9V 6F22 Alkaline Battery

* Battery Life: Over 120 Hours

Wiring Information:

Blue-Audio Red- Transmit Yellow-Receive (Black-Receive) Shield- Ground